



## Security Camera Solutions

### SD Cards as Storages in the Cameras



#### What you do

- Recording with low resolution to save storage capacity.
- Worry about data corruption & SD cards unrecognition.
- Develop cameras without checking program erase cycle.

#### What we offer

- SD cards which support 512MB to 256GB.
- SD cards with power failure protection.
- SD cards with P/E cycle monitoring function.

# Products lines

## ■ Fixed BOM models

Product		S Series				H Series							
NAND		MLC	Q-MLC	SLC		MLC		Q-MLC		SLC			
Class		10	10	6	10	4		4		6		6	
Capacity		8 to 256GB	4 to 128GB	512MB to 2GB	4 to 32GB	4 to 64GB		4 to 32GB		512MB to 2GB		4 to 16GB	
Temperature		-25 to 85°C	-25 to 85°C	-40 to 85°C	-40 to 85°C	0 to 70°C	-25 to 85°C	0 to 70°C	-25 to 85°C	0 to 70°C	-40 to 85°C	0 to 70°C	-40 to 85°C
Part number		NSDB-XXXGS(N**M)*S	NSDB-XXXGS(N**Q)*S	NSD6-XXXS(P**SEI)	NSDB-0XXXGS(N**SEI)	NSD4-XXXGH(B**MH)	NSD4-XXXGH(B**MHS)	NSD4-XXXGH(B**QH)	NSD4-XXXGH(B**QHS)	NSD6-XXXH(A**SD)	NSD6-XXXH(A**SDI)	NSD6-XXXGH(B**SE)	NSD6-XXXGH(B**SEI)
Operating Voltage		2.7~3.6V											
Dimensions(mm)		24(W) x 32(L) x 2.1(H)											
Transfer Speed (Typ.)	READ (non-UHS)	-	-	19	-	21		21		20		20	
	WRITE (non-UHS)	-	-	15	-	19		19		12		16	
Sequential Read/Write MB/s	READ (UHS)	89	90	-	89	73		74		-		33	
	WRITE (UHS)	73	80	-	70	42		63		-		27	
Static Wear Leveling		Yes											
Power failure protection function		Yes											
Refresh function		Yes											
Write Protect		Yes											
Fixed Specification		Yes(Fixed BOM)											
RoHS		Yes											
Lifetime diagnosis		Yes (Dedicated tool support)					Yes (Send back)						
Environmental documents		Yes											

## ■ Fixed Main Parts models

Product		K Series							
NAND		MLC		SLC				TLC	
Class		6	10	2		6	10		10
Capacity		2GB	4 to 128GB	128MB		1 to 2GB	4 to 16GB		16 to 256GB
Temperature		-25 to 85°C	-25 to 85°C	-25 to 85°C	-40 to 85°C	-25 to 85°C	-25 to 85°C	-40 to 85°C	-25 to 85°C
Part number		NSD6-xxxGK(L**M)HI	NSDB-xxxGK(L**M)HI	NSD2-128MK(L00SEI)	NSD6-xxxK(L00SEZ)	NSD6-xxxK(L00SEI)	NSDB-xxxGK(L00SEI)	NSDB-xxxGK(L00SEZ)	NSDB-xxxGK(R00TJS)
Operating Voltage		2.7~3.6V							
Dimensions(mm)		24(W) x 32(L) x 2.1(H)							
Transfer Speed (Typ.)	READ (non-UHS)	21	-	19		19	19		-
	WRITE (non-UHS)	20	-	18		18	18		-
Sequential Read/Write MB/s	READ (UHS)	-	90	88		88	88		86
	WRITE (UHS)	-	63	79		79	79		29
Static Wear Leveling		Yes							
Power failure protection function		Yes							
Refresh function		Yes							
Write Protect		Yes							
Fixed Specification		Yes (Main parts)							
RoHS		Yes							
Lifetime diagnosis		Yes (Dedicated tool support)							



Hagiwara Solutions Co., Ltd.

**Shinobu Apostol ITO**  
Global marketing manager  
[Shinobu\\_Ito@hagisol.co.jp](mailto:Shinobu_Ito@hagisol.co.jp)  
Mobile: +81 80 2455 3408

■ Tokyo office  
2F, Kudan First Place, 4-1-28,  
Kudankita, Chiyoda-ku, Tokyo,  
Japan, 102-0073  
Landline: +81-3-3556-5016

<http://www.hagisol.com>

HSS20018-A01

- The company names and product names noted herein are trademarks or registered trademarks.
- The content of this catalog is subject to change without notice due to development and other factors.
- Hagiwara Solutions is not responsible for any loss or damage that may be incurred based to the content of this catalog.

■ Partner: